


POLY CRYSTALLINE MODULE

DM275-P156-60

60 x 6" / 265-275W

Wattages:

265 / 270 / 275



Technology

High module conversion efficiency through superior manufacturing technology



PID Free



Power-Positive Tolerance

Guaranteed power output(0/+3%)



Performance

High performance under low light conditions (Cloudy days, mornings and evenings)



Quality

Manufactured according to International Quality and Environmental Management Systems (ISO9001, ISO14001)



Value

Our vertically integrated business model allows for competitive pricing and great value

www.dmegcsolar.com

Superior Manufacturing-Quality Assurance




- All modules are manufactured using TQC & SPC quality control systems
- Advanced cell sorting to avoid electric mismatch
- 100% EL Test-before lamination & prior to shipment
- Comprehensive Safety and Reliability tests are performed

Power Output




- Our IP67 rated junction box improves module performance and stability
- High-performance connectors provide low resistance interconnection to ensure the full utilization of module output power

Warranty



- 10 Years Manufacturers Warranty
- 10 Years Warranty, 90% power output
- 25 Years Warranty, 80% power output

Visible Quality



- Durable, high-quality
- Rigid construction: 5400Pa & 2400Pa rated assembly



Electrical Specifications

* STC irradiance of 1000W/m² spectrum AM 1.5 and cell temperature of 25°C

Module Type	Pm(W)	Tolerance	Imp(A)	Vmp(V)	Isc(A)	Voc (V)	Module Efficiency
DM265-P156-60	265	0/+3%	8.63	30.71	9.12	38.23	16.19%
DM270-P156-60	270	0/+3%	8.74	30.89	9.21	38.41	16.50%
DM275-P156-60	275	0/+3%	8.85	31.08	9.30	38.59	16.80%

Mechanical Data

Cell Type	DMTP4B157x157
Cell Arrangement	60(6x10)
Module Structure	Glass/ EVA / Backsheet(white)
Glass Thickness	3.2mm
Application Class	Class A at IEC 61730
Junction Box Rating	IP 67
Cables	1000mm/4mm ²
Connector Type	05-6
Fire Rating Class	Class C

Maximum Ratings

Operating Temperature	-40°C to +85°C
Maximum Load Capacity	Snow 5400Pa / Wind 2400Pa
Maximum System Voltage	600V DC(UL) / 1000V DC(IEC)
Maximum Series Fuse Rating	15A
Number of Diodes	3


Packaging

* frame sizes (35mm/40mm) available upon request

Module Dimensions	1650x992x40mm	1650x992x35mm
Weight	19kg	18.2kg
Pallet Dimensions	1700x1130x1130	1700x1130x1130
Container	40' HQ	40' HQ
Pieces per Pallet	26	29
Pallets per Container	28	28
Pieces per Container	728	812
Gross Weight per Pallet	535kg	570kg
Gross Weight per Container	14,980kg	15,960kg


Temperature Characteristics

Nominal Operating Cell Temperature (NOCT)	45°C±2°C
Temperature Coefficient of Isc	+0.057%/°C
Temperature Coefficient of Voc	-0.308%/°C
Temperature Coefficient of Pmax	-0.406%/°C




Note:mm[inch]

Current-Voltage&Power-Voltage Curve(275W)



Temperature Dependence of Isc, Voc, Pmax



Hengdian Group DMEGC Magnetics Co., Ltd.
Hengdian Industrial Zone, Dongyang City
Zhejiang Province, China 322118

Tel: 0086-579-8658-8825 Fax: 0086-579-8655-4845
Email: solar@dmegc.com.cn
www.chinadmegc.com www.dmegcsolar.com