



SOLARIF

RISK MANAGEMENT

Certificate number: **PV 28112910**
Certificate holder: **Hengdian Group DMEGC Magnetics Co., Ltd.**

Valid from: **25.10.2019**
Expires on: **25.10.2020**

Solarif Risk Management B.V. declares, after a thorough risk assessment of amongst others the production lines, financial strength, environmental and labor conditions, that the modules mentioned below from the **Hengdian Group DMEGC Magnetics Co., Ltd.** factory located at **Hengdian Industrial Zone, Dongyang City, Zhejiang Province**, are approved.

The certificate is valid from **25.10.2019** until **25.10.2020** and as long as the company is not insolvent.

This certificate enables clients of **Hengdian Group DMEGC Magnetics Co., Ltd.** to purchase Solarif's unique inherent defect coverage in addition to Solarif's Operational all risk insurance, supporting and backing-up the manufacturer's warranty in case of inherent defect.

This insurance is exclusively available through Solarif Insurance.

For more information or a quotation, please contact us at +31 (0) 26 711 5050, by email support@solarif.com or visit our website www.solarif.com.

Date: **28.11.2019**

Xander Vendrig / Manager Risk management
Solarif Risk Management BV





SOLARIF

RISK MANAGEMENT

Certificate number: **PV 28112910**

Certificate holder: **Hengdian Group DMEGC Magnetics Co., Ltd.**

Valid from: **25.10.2019**

Expires on: **25.10.2020**

APPROVED MONO-CRYSTALLINE MODULES - 1000V DC				
<i>Model</i>	<i>Max. Power (Wp)</i>	<i>Tolerance</i>		<i>Number and size of cell</i>
DMxxx-M156-72 (xxx = 305 – 360)	305-360	±3%		72x156mmx156mm
DMxxx-M156-60 (xxx = 255 – 300)	255-300	±3%		60x156mmx156mm
DMxxx-M156-72 (xxx = 335 – 375)	335-375	±3%		72x156mmx156mm
DMxxx-M156-72BK (xxx = 335 – 375)	335-375	±3%		72x156mmx156mm
DMxxx-M156-60 (xxx = 280 – 310)	280-310	±3%		60x156mmx156mm
DMxxx-M156-60BK (xxx = 280 – 310)	280-310	±3%		60x156mmx156mm
DMHxxxM6-144SW (xxx = 340 – 385)	340-385	±3%		72(144*1/2)
DMHxxxM6-144BB (xxx = 340 – 385)	340-385	±3%		72(144*1/2)
DMHxxxM6-144BW (xxx = 340 – 385)	340-385	±3%		72(144*1/2)
DMHxxxM6-120SW (xxx = 280 – 320)	280-320	±3%		60(120*1/2)
DMHxxxM6-120BB (xxx = 280 – 320)	280-320	±3%		60(120*1/2)
DMHxxxM6-120BW (xxx = 280 – 320)	280-320	±3%		60(120*1/2)
DMxxx-M156-72P (xxx = 335 – 375)	335-375	±3%		72x156mmx156mm
DMxxx-M156-60P (xxx = 280 – 310)	280-310	±3%		60x156mmx156mm
DMxxx-M156-36P (xxx = 175 – 190)	175-190	±3%		36x156mmx156mm
DMxxx-M159-72 (xxx = 385 – 395)	385-395	±3%		72x159mmx159mm





SOLARIF

RISK MANAGEMENT

DMxxx-M159-72BK (xxx = 385 – 395)	385-395	±3%		72x159mmx159mm
DMxxx-M159-60 (xxx = 315 – 325)	315-325	±3%		60x159mmx159mm
DMxxx-M159-60BK (xxx = 315 – 325)	315-325	±3%		60x159mmx159mm
DMHxxxM6A-144SW (380 – 405)	380-405	±3%		72(144*1/2)
DMHxxxM6A-144BB (xxx = 380 – 405)	380-405	±3%		72(144*1/2)
DMHxxxM6A-144BW (xxx = 380 – 405)	380-405	±3%		72(144*1/2)
DMHxxxM6A-120SW (xxx = 320 – 335)	320-335	±3%		60(120*1/2)
DMHxxxM6A-120BB (xxx = 320 – 335)	320-335	±3%		60(120*1/2)
DMHxxxM6A-120BW (xxx = 320 – 335)	320-335	±3%		60(120*1/2)

APPROVED MONO-CRYSTALLINE MODULES - 1500V DC				
Model	Max. Power (Wp)	Tolerance		Number and size of cell
DMxxx-M156-72 (xxx = 335 – 375)	335-375	±3%		72x156mmx156mm
DMxxx-M156-60 (xxx = 280 – 310)	280-310	±3%		60x156mmx156mm
DMHxxxM6-144SW (xxx = 340 – 385)	340-385	±3%		72(144*1/2)
DMHxxxM6-120SW (xxx = 280 – 320)	280-320	±3%		60(120*1/2)
DMxxx-M156-72P (xxx = 335 – 375)	335-375	±3%		72x156mmx156mm
DMxxx-M156-60P (xxx = 280 – 310)	280-310	±3%		60x156mmx156mm
DMxxx-M156-36P (xxx = 175 – 190)	175-190	±3%		36x156mmx156mm
DMxxx-M159-72 (xxx = 385 – 395)	385-395	±3%		72x159mmx159mm
DMxxx-M159-60 (xxx = 315 – 325)	315-325	±3%		60x159mmx159mm
DMHxxxM6A-144SW (xxx = 380 – 405)	380-405	±3%		72(144*1/2)
DMHxxxM6A-120SW (xxx = 320 – 335)	320-335	±3%		60(120*1/2)





SOLARIF

RISK MANAGEMENT

APPROVED (HALF-CUT BIFACIAL DOUBLE GLASS) MONO-CRYSTALLINE MODULES - 1500V DC				
<i>Model</i>	<i>Max. Power (Wp)</i>	<i>Tolerance</i>		<i>Number and size of cell</i>
DMGxxxB6-72ST (xxx = 355 – 375)	355-375	±3%		72x156mmx156mm
DMGxxxB6-60ST (xxx = 295 – 315)	295-315	±3%		60x156mmx156mm
DMGxxxB6-72BT (xxx = 355 – 375)	355-375	±3%		72x156mmx156mm
DMGxxxB6-60BT (xxx = 295 – 315)	295-315	±3%		60x156mmx156mm
DMGxxxB6-144HST (xxx = 360 – 385)	360-385	±3%		72(144*1/2)
DMGxxxB6-120HST (xxx = 310 – 330)	310-330	±3%		60(120*1/2)
DMGxxxB6-144HBT (xxx= 360 – 385)	360-385	±3%		72(144*1/2)
DMGxxxB6-120HBT (xxx = 310 – 330)	310-330	±3%		60(120*1/2)

APPROVED POLY-CRYSTALLINE MODULES - 1500V DC				
<i>Model</i>	<i>Max. Power (Wp)</i>	<i>Tolerance</i>		<i>Number and size of cell</i>
DMxxx-P156-72 (xxx = 320 – 355)	320-355	±3%		72x156mmx156mm
DMxxx-P156-60 (xxx = 270 – 295)	270-295	±3%		60x156mmx156mm
DMHxxxP6-144 (xxx = 315 – 340)	315-340	±3%		72(144*1/2)
DMHxxxP6-120 (xxx = 270 – 295)	270-295	±3%		60(120*1/2)





SOLARIF
RISK MANAGEMENT

APPROVED (DOUBLE GLASS) POLY-CRYSTALLINE MODULES - 1500V DC				
Model	Max. Power (Wp)	Tolerance	Efficiency	Number and size of cell
DMGxxxM6-60BT (xxx = 255 – 310)	255-310	±3%		60x156mmx156mm
DMGxxxM6-60XW (xxx = 255 – 310)	255-310	±3%		60x156mmx156mm
DMGxxxM6-60BW (xxx = 285 – 310)	255-310	±3%		60x156mmx156mm
DMGxxxM6-60XT (xxx = 255 – 310)	255-310	±3%		60x156mmx156mm
DMGxxxM6-60ST (xxx = 255 – 310)	255-310	±3%		60x156mmx156mm
DMGxxxM6-60SW (xxx = 255 – 310)	255-310	±3%		60x156mmx156mm
DMGxxxM6-60BB (xxx = 255 – 310)	255-310	±3%		60x156mmx156mm



Solarif Risk Management BV
Mr. B.M. Teldersstraat 11 | 6842 CT Arnhem | PO Box 4192 | 6803 ED Arnhem | The Netherlands
T. +31 (0)26 711 5050 | info@solarif.com | www.solarif.com | IBAN NL93RABO0302073744
COC 09193608 | VAT NL820465148B01